

A standard linear barcode is positioned vertically on the left side of the page. It is composed of vertical black lines of varying widths on a white background.

	Class	Subclass

U.S. UTILITY Patent Application

O.I.P.E.

PATENT DATE

MAK SCANNED TO 3 Q.A. TM

APPLICATION NO. 09/828203	CONT/PRIOR D F	CLASS 073	SUBCLASS 023.200	ART UNIT 2855	EXAMINER Cygma
------------------------------	-------------------	--------------	---------------------	------------------	-------------------

Toby Matheram
Steven Vass
Colin Houghton

Apparatus and methods relating to humidified air and to sensing
components of gas or vapour

PTO-2040
12/02

BEST AVAILABLE COPY

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____ _____ _____				ISSUE FEE	
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed.				Amount Due	Date Paid
				ISSUE BATCH NUMBER	

WARNING:

WARNING: The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A
(Rev. 6/98)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)